



## "WORLDWIDE SERIES" CYLINDERS

**4500 / 5000 / 6000 PSI**

**AVAILABLE NOW WITH 10 YEAR RETEST**

YOU CAN NOW TAKE ADVANTAGE OF THE LATEST IN CYLINDER TRANSPORTABILITY. NORRIS INTRODUCES ITS "**WORLDWIDE SERIES**" OF LIGHT WEIGHT 4500-6000 PSI CYLINDERS THAT CAN BE FILLED AND TRANSPORTED ACROSS MOST OF THE WORLD'S BORDERS & BEST OF ALL, OFFERS A 10 YEAR RE-TEST INTERVAL. AVAILABLE IN THE TRADITIONAL U.S. STANDARD 3/4" -14 VALVE INLET THREADS OR THE EUROPEAN STANDARD 25E THREADS THAT HAVE DEMONSTRATED SUPERIOR LEAK RESISTANT PERFORMANCE FOR YEARS, EFFECTIVELY REDUCING THE OPPORTUNITY OF VALVE CONNECTION LEAKS. TPED (Pi) AVAILABLE UPON REQUEST.



**CYLINDERS DESIGNED UNDER SPECIFICATION ISO 9809-PARTS 1 & 2;  
AND ARE DOT QUALIFIED CYLINDERS UNDER THE UN REGULATIONS.**

### Contact Information

Norris Cylinder Company  
4818 W. Loop 281  
Longview, TX 75603

[sales@norriscylinder.com](mailto:sales@norriscylinder.com)  
[www.norriscylinder.com](http://www.norriscylinder.com)  
phone: 1 800 527-8418  
fax: 903 237-7654  
or contact your Regional Sales Manager

Model	Service Pressure		Length		Diameter		Water Volume		Weight		Air Capacity	
	psi	bar	in	mm	in	mm	cu in	liters	lbs	kg	cu ft	cu m
8HP501C	4500	310	51	1295	9.4	239	2750	45	155	70.3	437.1	12.38
8HP536C	5000	345	52.5	1333	9.4	239	2750	45	170	77.1	472	13.37
8HP586C	6000	414	52	1320	9.4	239	2641	43.3	195	88.4	510.5	14.46

Manufactured in Longview, TX. USA